

ŻURAW 16 T CKD AD 160

Wysięg [m]	Podpory wysunięte 360°					Podpory opuszczone 360°		Transport na haku T dl. wys. 7,7 m [kg]
	B dl. wys. 7,7 m [kg]	D dl. wys. 12,2 m [kg]	E dl. wys. 16,6 m [kg]	F dl. wys. 20 m [kg]	G dl. wys. 20,8 m [kg]	A dl. wys. 7,7 m [kg]	C dl. wys. 12,2 m [kg]	
2,0	16 000	10 000				9 000	7 500	4 000
2,5	16 000	10 000	5 000			9 000	7 500	4 000
2,8	16 000	10 000	5 000			9 000	7 500	3 500
3,0	16 000	10 000	5 000			8 150	7 500	3 250
3,2	16 000	10 000	5 000			7 500	7 500	3 030
3,5	16 000	10 000	5 000			6 550	6 550	2 730
3,8	16 000	10 000	5 000			5 860	5 860	2 470
4,0	14 900	10 000	5 000		2 000	5 450	5 450	2 330
4,25	13 700	10 000	5 000		2 000	5 000	5 000	2 160
4,5	12 600	10 000	5 000		2 000	4 550	4 550	1 970
4,75	11 600	10 000	5 000		2 000	4 160	4 160	1 840
5,0	10 650	10 000	5 000		2 000	3 840	3 840	1 700
5,2	10 000	10 000	5 000		2 000	3 600	3 600	1 600
5,5	9 050	9 050	5 000		2 000	3 250	3 250	1 450
6,0	7 760	7 760	5 000	2 000	2 000	2 800	2 800	1 250
6,5	6 800	6 800	5 000	2 000	2 000	2 450	2 450	1 040
7,0	6 000	6 000	5 000	2 000	2 000	2 140	2 140	960
7,2	5 700	5 700	5 000	2 000	2 000	2 000	2 000	800
7,8		5 000	5 000	2 000	2 000		1 730	
8,0		4 750	4 750	2 000	2 000		1 640	
9,0		3 850	3 850	1 600	1 500		1 250	
10,0		3 200	3 200	1 350	1 150		1 000	
11,0		2 700	2 700	1 120	930			
11,7		2 400	2 400	1 040	810			
12,0			2 250	1 000	800			
13,0			1 900	900	700			
14,0			1 650	850	640			
15,0			1 400	800	600			
16,2			1 200					